

AM WINGLETS

AM DISCRETE SYSTEM

Discrete AM (Acousto-Magnetic) system designed with a focus on strong detection of adhesive labels, reliability, and flexibility. The AM WINGLETS system is an NG (Next Generation) product line that is suitable for protection of standard retail exits.

The slim door winglets are mounted on the sides of the entrance or on the door frame for a discrete yet powerful solution that compares to our standard AM pedestals. The clear acrylic panel allows it to blend seamlessly into modern or premium retail spaces, with no disruption to the surface of the floor. The store retains a more inviting look by having the security system out of direct sight.

A fully equipped security solution includes integrated visitor counting and directional alarms. It can also be connected to the StoreMonitor cloud or upgraded with wireless communication for easy data collection and maximum security.

STOREMONITOR COMPATIBLE ...



Features & options:

- Remote maintenance and diagnostics
- Wireless communication
- StoreMonitor connectivity
- Visitor counting
- Smart directional alarms
- Power saving mode
- Additional alarm outputs
- · Jammer detector
- Tag too close indication



Performance: ★★★☆









Integrated smart visitor counting and data collection through our StoreMonitor cloud application will provide you with essential data you need, not only to monitor the system functionality and status, but to provide valuable insights into your store performance and sales efficiency.



Remote connectivity with our eComm module ensures that our systems are not only easy to install but can also be serviced and maintained remotely with fast response and without unnecessary travel costs.



On top of remote connectivity our WINGLETS system now features optional **wireless in-store communication** which makes the installation and maintenance of the system very flexible and cost effective. Setting up and adjusting our system has never been easier or faster.

| | AM WINGLETS |
|--|--------------------|
| FEATURES / OPTIONS | 7 |
| DISCREET SYSTEM | ~ |
| INTEGRATED METAL AND MAGNET DETECTION ^{3,6} | × |
| INTEGRATED VISITOR COUNTING ^{3,5} | V |
| SMART DIRECTIONAL ALARMS ³ | V |
| REMOTE MAINTENANCE AND DIAGNOSTICS ⁵ | 0 |
| WIRELESS COMMUNICATION | 0 |
| DECORATION LIGHT | ~ |
| POWER SAVING MODE | ~ |
| COLOUR OPTIONS | S/B/W |
| | |
| DIMENSIONS | |
| HEIGHT | 170.0 cm |
| WIDTH | 26.3 cm |
| DEPTH (PCB COVER) | 4.6 cm |
| PLEXIGLASS THICKNESS | 2.0 cm |
| WEIGHT | 11 kg |
| | |
| DETECTION RANGE | |
| DETECTION RANGE SOFT LABELS ¹ | DUAL |
| | up to 200 cm |
| DETECTION RANGE HARD TAG ² | DUAL |
| | up to 250 cm |
| | |
| PRODUCT CODES | 1 pair of antennas |
| SILVER COLOUR | AS-WINGS |



Legend: ✓ included X not available O optional.

¹tested with original DR labels in all orientations. ²tested with original AMERSEC® pencil tags in all orientations. ³minimum of 2 pedestals required. ⁴visitor counting sensors required. ⁵e-COMM communication module required with a Storemonitor account. ⁶MMS Controller unit required.

System specification

Operating frequency – 58 kHz Power – 110–240 V, 50–60 Hz Consumption – 120 W

