

ACE ALUPROFI PLEXI 50, ACE ALUPROFI 40, ACE ALUPROFI 50

AM ACE PEDESTALS

Highly efficient AM (Acousto-Magnetic) system designed to operate as a powerful and reliable single pedestal with up to two additional receivers. The proven aluminum frame design of the ALUPROFI pedestal is very durable yet aesthetically appealing and includes space for advertisement banners, which makes the AM ACE system a perfect solution for cash desks or small to medium sized entrances. If visual transparency is a priority over printed advertising, our ALUPROFI PLEXI design is the perfect solution.

A fully equipped security solution includes integrated visitor counting and directional alarms. It can also be connected to the StoreMonitor cloud or upgraded with wireless communication for easy data collection and maximum security.

STOREMONITOR COMPATIBLE 

Features & options:

- Remote maintenance and diagnostics
- Wireless communication
- StoreMonitor connectivity
- Visitor counting
- Advertisement space
- Smart directional alarms
- Power saving mode
- Additional alarm outputs
- Jammer detector
- Tag too close indication





Integrated smart visitor counting and data collection through our StoreMonitor cloud application will provide you with essential data you need, not only to monitor the system functionality and status, but to provide valuable insights into your store performance and sales efficiency.



Remote connectivity with our eComm module ensures that our systems are not only easy to install but can also be serviced and maintained remotely with fast response and without unnecessary travel costs.



On top of remote connectivity our ACE system now features **wireless in-store communication** which makes the installation and maintenance of the system very flexible and cost effective. Setting up and adjusting our system has never been easier or faster.



An **advertisement space** is a standard feature of all ALUPROFI models of AMERSEC® pedestals. Use your security system as an additional sales tool with our “easy slide” access to printed banner replacement. An identical pedestal but without the opaque panel, the ALUPROFI PLEXI features a transparent acrylic surface that blends in with the surrounding space.

Design comparison

PEDESTAL COMPARISON	ALUPROFI 40	ALUPROFI 50	ALUPROFI PLEXI 50
FEATURES / OPTIONS			
ADVERTISING PANEL	✓	✓	✗
INTEGRATED METAL AND MAGNET DETECTION ^{3,6}	✗	✗	✗
INTEGRATED VISITOR COUNTING ^{3,5}	○	○	○
SMART DIRECTIONAL ALARMS ^{3,4}	○	○	○
REMOTE MAINTENANCE AND DIAGNOSTICS ⁵	○	○	○
WIRELESS COMMUNICATION	○	○	○
POWER SAVING MODE	✓	✓	✓
COLOUR OPTIONS	S / B / W	S / B / W	S / B / W
DIMENSIONS			
HEIGHT	152.5 cm	152.5 cm	152.5 cm
WIDTH	38.7 cm	55.3 cm	55.3 cm
DEPTH	6.2 cm	6.2 cm	6.2 cm
ADVERTISING PANEL	1456 × 303 mm	1456 × 469 mm	✗
WEIGHT MASTER/RECEIVER	13.5 kg / 9.2 kg	18.5 kg / 14.4 kg	15.9 kg / 12.9 kg
DETECTION RANGE			
DETECTION RANGE SOFT LABELS ¹	MONO / DUAL up to 100 / 200 cm	MONO / DUAL up to 110 / 220 cm	MONO / DUAL up to 110 / 220 cm
DETECTION RANGE HARD TAG ²	MONO / DUAL up to 140 / 280 cm	MONO / DUAL up to 150 / 300 cm	MONO / DUAL up to 150 / 300 cm
PRODUCT CODES			
SILVER COLOUR	MASTER / RECEIVER AS-A40S/AS-AR40S	MASTER / RECEIVER AS-A50S/AS-AR50S	MASTER / RECEIVER AS-A50PS/AS-AR50PS

Legend: ✓ included ✗ not available ○ optional.

¹tested with original DR labels in all orientations. ²tested with original AMERSEC® pencil tags in all orientations. ³minimum of 2 pedestals required.

⁴visitor counting sensors required. ⁵e-COMM communication module required with a Storemonitor account. ⁶MMS Controller unit required.

System specification

Operating frequency – 58 kHz
Power – 110-240 V, 50-60 Hz
Consumption – 120 W

